

# Xerox® WorkCentre® 6655i Colour Multifunction Printer

The WorkCentre 6655i Colour Multifunction Printer is built on Xerox® ConnectKey® Technology. For more information, go to **www.connectkey.com**.



System Specifications	WorkCentre 6655i/X	
Speed (Colour and Black and White)	Up to 36 ppm 8.5 x 11 in. Up to 35 ppm A4 / 210 x 297 mm Up to 29 ppm 8.5 x 14 in. / 216 x 356 mm	
Monthly Duty Cycle <sup>1</sup>	Up to 100,000 pages	
Recommended Average Monthly Print Volume <sup>2</sup>	Up to 10,000 pages	
Hard Drive / Processor / Memory	Minimum 250 GB / 1 GHz Dual-core / 4 GB	
Connectivity	10/100/1000Base-T Ethernet, High-Speed USB 2.0 direct print, Wi-Fi Direct with Optional Xerox® USB Wireless Adapter	
Controller Features	Unified Address Book, Remote Control Panel, Online Support (accessed from the user interface and print driver), Configuration Cloning	
Copy and Print		
Copy and Print Resolution	Copy: Up to 600 x 600 dpi; Print: Up to 2400 x 600 dpi	
First-print-out Time	As fast as 11 seconds colour / 11 seconds black and white	
First-copy-out Time	As fast as 16 seconds colour / 15 seconds black and white	
Page Description Languages	Adobe® PostScript® 3™, Adobe® PDF version 1.7, PCL® 5c / PCL 6, XML Paper Specification (XPS®)	
Print Features	Print from USB, Encrypted Secure Print, Xerox® Earth Smart Driver Settings, Job Identification, Store and Recall Driver Settings, Bidirectional Real-time Status, Scaling, Job Monitoring, Xerox® Colour By Words, Application Defaults, Two-sided Printing (as default), Hold All Jobs	
Mobile Printing and Apps	Standard: Apple® AirPrint™, Mopria® Certified, QR Code App, Xerox® App Gallery App, @PrintByXerox App; Free Download: Xerox® Print Service Plugin for Android, Mopria® Print Service Plug-in for Android™, Xerox® Mobile Link App; Optional: Xerox® Mobile Print, Xerox® Mobile Print Cloud, Xerox® Easy Translator Service	
Scan		
Standard Features	<b>Destinations</b> : Scan to Mailbox, Scan to USB, Scan to Email, Scan to Network; <b>File Formats</b> : PDF, PDF/A, XPS, JPEG, TIFF; <b>Convenience Features</b> : Scan to Home, Single Touch Scan, Searchable PDF, Single/Multi-page PDF/XPS/TIFF, Encrypted / Password Protected PDF, Linearised PDF / PDF/A	
Optional Features	ConnectKey® for DocuShare®, Xerox® Scan to PC Desktop® SE and Professional, numerous solutions available through various Xerox Alliance Partners	
Fax		
Standard Features	Walk-up Fax³, LAN Fax, Internet Fax (includes LAN Fax (Fax forward to Email or SMB)), Network Server Fax Enablement	
Security		
Standard Features	McAfee® Embedded, McAfee ePolicy (ePO) Compatible, HDD Overwrite, AES 256-bit Encryption (FIPS 140-2 compliant), SHA-256 Hash Message Authentication, Common Criteria Certification (ISO 15408) (undergoing evaluation), Encrypted Secure Print, Secure Fax, Secure Scan, Secure Email, Cisco® TrustSec Identity Services Engine (ISE) Integration, Network Authentication, TLS, SNMPv3, Audit Log, Access Controls, User Permissions	
Optional Features	McAfee Integrity Control, Smart Card Enablement Kit (CAC/PIV/.NET), Xerox® PrintSafe Software	
Accounting		
Standard Features	Xerox® Standard Accounting (Copy, Print, Scan, Fax, Email), Network Accounting Enablement	
Optional Features	Equitrac Express®, Equitrac Office®, YSoft® SafeQ®, other network accounting solutions available through various Xerox Alliance Partners	

Device Specifications				
Control Panel Languages				
control runer Euriguages	Danish, Finnish, Turkish, Greek, Russiar		iational Spanish, Butch, Brazilian Fortag	guese, swedish, Morwegian,
Accessories				
Optional Accessories	550-sheet Feeder Stand Smart Card Enablement Kit Wi-Fi Direct with Optional Xerox® USB Wireless Adapter McAfee® Integrity Control Enablement Kit			
Electrical Requirements	3 3			
North America	Voltage: 110-127 VAC +/- 10%; Frequ	uencv: 50/60 Hz +/- 3%, 10 A		
Europe	Voltage: 220-240 VAC +/- 10%; Frequ			
Power Consumption				
Running (Average)	110V: 564.8 watts 220V: 486.4 watts			
Standby Mode <sup>4</sup>	110V: 69.7 watts 220V: 71.0 watts			
Low Power Mode <sup>4</sup>	110V: 2.6 watts 220V: 2.7 watts			
Auto Off / Sleep Mode <sup>4</sup>	110V: 0.0 watts 220V: 0.0 watts			
Warm-up	Time from power off to when services	are displayed: As fast as 160 seconds		
Low Power Recovery	<17 seconds	·		
Operating Environment	1			
Required Temperature Range	41° to 90° F (5° to 32° C)			
Required Relative Humidity	15% to 85%			
Sound Power Levels	Operating 6.76 B(A), Standby: 4.14 B(A)			
Sound Pressure Levels	Operating: 51.8 dB(A), Standby: 25.1			
Dimensions and Weight	Width	Depth	Height	Weight
(Unpackaged)		•		-
WorkCentre 6655i/X	21.2 in. / 538 mm	21.8 in. / 553 mm	24.6 in. / 625 mm	82.9 lbs. / 37.6 kg
550-sheet Feeder	19.2 in. / 488 mm	19.2 in. / 488 mm	5.5 in. / 138 mm	9.7 lbs. / 4.4 kg
Stand	29 in. / 737 mm	27.5 in. / 699 mm	13.1 in. / 332 mm	28.4 lbs. / 12.9 kg
Dimensions and Weight (Packaged)	Width	Depth	Height	Weight
WorkCentre 6655i/X	26.4 in. / 671 mm	26.6 in. / 675 mm	29.6 in. / 751 mm	96.8 lbs. / 43.9 kg
550-sheet Feeder	23.9 in. / 607 mm	23.5 in. / 596 mm	9.4 in. / 239 mm	13.7 lbs. / 6.2 kg
Stand	22 in. / 560 mm	20.9 in. / 530 mm	10.6 in. / 270 mm	36.6 lbs. / 16.6 kg
Certifications				
	FCC Part 15, Class A FCC Part 68 CE Mark applicable to Directives 2006/95/EC, 2004/108/EC and 1999/5/EC UL 60950-1/CSA 60950-1-07, 2nd Edition EAC WEEE Directive 2002/96/EC and FDA/CDRH—Class 1 Laser Product CE mark applicable Directive 2011/65/EC (RoHS) Common Criteria (IEEE 2600.2 standard) (undergoing evaluation) NOM Apple® AirPrint™ 1.4 Certification Mopria® Certified Wi-Fi Direct Certification Ukraine Blue Angel (undergoing evaluation) ECOLOGO® (undergoing evaluation) EPEAT (United States) Citrix ENERGY STAR® qualified To view the latest list of certifications, go to www.xerox.com/OfficeCertifications.			
Paper Handling				
Duplex Automatic Document Feed	er (DADF)			
Capacity <sup>5</sup>	60 sheets			
Speed	Lin to E/Limenta and the first No.	tor / E1 ipm A / /-i		
Black and white	Up to 54 images per minute (ipm) Letter / 51 ipm A4 (simplex) Up to 25 ipm Letter / 24 ipm A4 (duplex)			
Colour	Up to 29 ipm Letter / 28 ipm A4 (simplex) Up to 14 ipm Letter / 13 ipm A4 (duplex)			

Paper Sizes Sensed	5.5 x 5.5 in. to 8.5 x 14 in. / 139.7 x 139.7 mm to 216 x 356 mm		
Weights	Simplex: 13 lb. bond to 32 lb. bond / 50 gsm to 125 gsm Duplex: 16 lb. bond to 32 lb. bond / 60 gsm to 125 gsm		
Bypass Tray			
Capacity⁵	150 sheets		
Sizes	Custom sizes: 3 x 5 in. to 8.5 x 14 in. / 76.2 x 127 mm to 216 x 356 mm		
Weights	16 lb. bond to 80 lb. cover / 60 to 220 gsm		
Types	Plain Punched Letterhead Lightweight Cardstock, Lightweight Glossy Cardstock, Glossy Cardstock, Cardstock Recycled Bond Labels Pre-printed Envelopes Custom		
Trays 1			
Cαpacity⁵	550 sheets		
Sizes	Custom Sizes from 5.8 x 8.3 in. to 8.5 x 14 in. / 148 x 210 mm to 216 x 356 mm		
Weights	16 lb. bond to 80 lb. cover / 60 to 216 gsm		
Types	Plain Punched Letterhead Lightweight Cardstock, Cardstock Recycled Bond Labels Pre-printed Custom		
1 Additional Tray			
Capacity⁵	550 sheets		
Sizes	Custom Sizes from 5.8 x 8.3 in. to 8.5 x 14 in. / 148 x 210 mm to 216 x 356 mm		
Weights	16 lb. bond to 80 lb. cover / 60 to 216 gsm		
Types	Plain Punched Letterhead Lightweight Cardstock, Lightweight Glossy Cardstock, Glossy Cardstock (simplex only), Cardstock (simplex only) Recycled Bond Labels Pre-printed		
Total Capacity	Custom		
Device Standard Capacity <sup>5</sup>	700 sheets		
Device Total Capacity <sup>5</sup>	1,250 sheets		
Paper Output			
Capacity	250 sheets face down with tray full sensor		
Offline Convenience Stapler	250 Sieces dec domi mui day idii selisor		
Capacity <sup>5</sup>	20-sheet stapling, single position		
Сору	20 Street Stapung, Striget position		
Speed (Colour and Black and White)	Up to 36 ppm 8.5 x 11 in. Up to 35 ppm A4 / 210 x 297 mm Up to 29 ppm 8.5 x 14 in. / 216 x 356 mm		
First-copy-out Time	As fast as 16 seconds colour / 15 seconds black and white		
Sides (input:output)	1-1, 1-2, 2-2, 2-1		
Quantity	1 to 9,999		
Resolution (max.)	Up to 600 x 600 dpi		
Reduction / Enlargement	Variable zoom from 25% to 400% in 1% increments		
Concurrency	Programme-ahead to allow job to be initiated while initial job is processed (Copy, Print, Fax and Scan)		
	1 2 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1		

Copy Features	Annotation and Bates™ stamping (with colour capability and font size adjustment) Authentication for Services Auto Paper Select Auto Reduction & Enlargement to fit selected paper size Auto Tray Switching Automatic 2-sided / Duplex Booklet Creation Build Job: (Enables page-level programming and also lets you proof each section or delete last section as the job is built) Collation Covers (Front only, front and back, back only, printed inside and out: Blank or Printed) Dividers (blank) Edge Erase Features Help (Intuitive text and graphic descriptions) ID Card Copy Image Quality Adjustments Image Shift (with Auto Centre option) Invert Image (negative or mirror image) Large Job Interrupt Multi-up (up to 15 columns by 15 rows) Sample Set Save Job Settings Stapling	
Xerox <sup>®</sup> Copier Assistant <sup>®</sup>	Xerox® Copier Assistant® Software provides a PC-based alternative to the user interface touchscreen. Used in conjunction with a customer-supplied PC attached via the USB port, this software supports text-to-speech, screen magnification and easy PC keyboard access to basic and advanced copfeatures. Section 508-compliant. For more information or to download Xerox® Copier Assistant for free, visit www.xerox.com.	
Print		
First-print-out Time	As fast as 11 seconds colour / 11 seconds black and white	
Print Resolution	Up to 2400 x 600 dpi	
Print Features	Application Defaults	
Print from USB	Banner Sheet Enable / Disable Bidirectional Real-time Status Booklet Printing Cover Selection Delay Print (specific time) User Permissions Image Options (Toner Saver, Standard and High Resolution) Job Identification (Print ID or Banner, Print ID in margins on first page only or all pages) LAN Fax (requires optional Fax Kit) Layout / Watermark N-up (up to 16 pages per sheet) Booklet layout Finishing Fit to new paper size Hold All Jobs Paper Selection by Attribute Print Around Proof Print Sample Set Saved Job Secure Print with Timed Deletion Special Pages (exception page programming: covers, inserts, exception pages) Store and Recall Driver Settings Sustainability Features (Xerox® Earth Smart Settings, Duplex, N-up, Turn-off Banner and Print ID, Smart Sample Set, Hold All Jobs) Two-sided Printing (as default)  Allows walk-up printing from Type A USB port	
PHILL HOIH USB	Supported file formats: PDF, JPEG, TXT, TIFF, PS, XPS, PCL	
Operating Systems	Microsoft® Windows® XP SP3 (32- and 64-bit) Windows Server 2003 SP2 R2 (32- and 64-bit) Windows Server 2008 and R2 (32- and 64-bit) Windows Server 2012 and R2 (64-bit) Windows Vista SP2 (32- and 64-bit) Windows 7 (32- and 64-bit) Windows 8 (32- and 64-bit) Windows 8.1 (32- and 64-bit) Windows 10 (32- and 64-bit) Mindows 10 (32- and 64-bit) Mac OS 10.8, 10.9, 10.10, 10.11 Linux® Redhat® Fedora® Core 20 x86 Ubuntu® 14.04 x64 openSUSE® 13.1 x64	
Network Protocols	TCP/IP: HTTP/HTTPS, Internet Printing Protocol, LPR/LPD, Raw Socket Printing/Port 9100, IPv4/IPv6,WSD  NetWare: Bindery and NDS IPX/SPX, NDPS®/NEPS (with Server Gateway)  AppleTalk®: EtherTalk®  Microsoft Windows Networking over IP  Bonjour® / AirPrint™  IPv6  Secure FTP	

Administrative Protocols	DHCP, SNMP, WINS, SLP® v2, HTTP, HTTPS, DHCP Autonet, TLS, NTP, MDNS, SSDP		
Fonts	PCL: 93 scalable fonts, line printer and bitmap font (including Cyrillic font support)		
	PostScript 3: 173 Type 1 fonts, 2 Multiple Master fonts		
Xerox <sup>®</sup> Mobile Express Driver <sup>®</sup>	Makes it easy for mobile users to find, use and manage Xerox® and non-Xerox devices in every new location. Plug into a new network, and Mobile Express Driver automatically discovers available printers and provides status and capability information. Save a list of "favourite" printers for each location, store application print settings for use on any printer in any network, and greatly reduce mobile support calls to IT.		
Xerox® Global Print Driver®	A truly universal print driver that lets IT administrators install, upgrade and manage Xerox® and non-Xerox devices from a single driver. It provides a consistent, easy-to-use interface for end-users, reducing the number of support calls, and simplifying print services management.		
Xerox® Pull Print Driver	Makes it easy for IT managers to qualify, deploy and manage all print devices using a single driver in a Pull Print environment. Uses a single queue and single driver. The Xerox® Pull Print Driver extends convenience across a broad range of printing assets. IT administrators no longer need to manage and configure multiple drivers. Used in conjunction Equitrac Office®, Ysoft® SafeQ®, Pharos® and others.		
Print Solutions			
Xerox® Mobile Print Cloud (Optional)	Xerox® Mobile Print Cloud addresses the needs of businesses with a mobile workforce and puts you ahead of the evolving mobile print need, but without burdening staff, budget or infrastructure. Getting started takes only a few minutes via the cloud. Print from any mobile device to nearly any brand of printer. Accurate printing with true Microsoft® Office® rendering and more. Print what you need, when, where and how you need it.		
Xerox® Mobile Print Solution (Optional)	Xerox® Mobile Print Solution is an ideal choice for sites that have additional requirements for control and security with an onsite server. Xerox® Mobile Print Solution allows users to print from most mobile devices to nearly any brand of printer or multifunction printer without drivers or added complexity. Simply enter a release code (PIN) at the device and get accurate printing with true Microsoft Office rendering and more to use with your server for private, onsite deployment.		
Xerox® Print Service Plug-in for Android™ (Free at Google Play™ Store)	The Xerox® Print Service Plug-in for Android KitKat (4.4 or greater) devices streamlines mobile printing without third-party apps or additional print drivers. You can easily print photos, Web pages and documents when your mobile device is connected to ConnectKey-enabled multifunction printers using a wireless network. A robust print option set includes two-sided printing, stapling and secure code release. A free download is available from the Google Play™ store.		
Xerox® Mobile Link App (Free at Google Play Store and Apple® App Store)	The Xerox® Mobile Link App allows you to scan, email and fax from your phone or tablet by connecting with our multifunction printers and send data to and print data from cloud storage. It is easy to create Mobile Link One-Touch Workflows between a mobile device and a multifunction printer.  Using a manual address or QR code identification for pairing, automatic device discovery makes it easy to find and pair a mobile device with a nearby Xerox® multifunction printer.		
Unified Address Book for Fax, Inte	ernet Fax, Email and Scan to		
Features	Services supported: Fax, Internet Fax, Email, Scan to Maximum contacts: 5,000 Contacts: Supports 1 or more destinations Favourites for quick access of fax numbers, emails, etc.		
Scan			
Concurrency	Scan while the system is printing, copying, or while it is transferring scan to network or fax jobs (priority is for return of scanned originals and printing concurrent jobs)		
Speed			
Black and white	Up to 54 images per minute (ipm) Letter / 51 ipm A4 (simplex) Up to 25 ipm Letter / 24 ipm A4 (duplex)		
Colour	Up to 29 ipm Letter / 28 ipm A4 (simplex) Up to 14 ipm Letter / 13 ipm A4 (duplex)		
Resolution	72 x 72 dpi to 600 x 600 dpi Bit Depth: 1-bit (black and white), 8-bit (greyscale), 24-bit (colour)		
Maximum Scan Area	Up to 8.5 x 14 in. / 216 x 356 mm		
Scan Template Management	Support 250 scan templates Create Xerox® CentreWare® IS scan templates and share via device cloning to other multifunction printers Confirmation sheet options		
Network Protocols	sFTP, FTP, SMB, NetWare, HTTP, HTTPS		
File Compression	Colour TIFF (TIFF 6.0 or TTN2 with JPEG, LZW) Black and white TIFF (G3MH, G4 MMR compression–single or multiple pages) Searchable PDF/OCR and PDF/A-1b (MRC, JPEG, G3 MH, G4 MMR, JBIG 2 Huffman, JBIG Arithmetic Compression, Deflate (for Black and white and within MRC)) Encrypted / Password Protected PDF (Network Scan Templates only) Linearised PDF, PDF/A		
Document Management Fields (Meta Data)	Features only available in Network Scan to File Templates:  • 1 to 6 user programmable metadata fields per network scan to file templates and unlimited fields within the template – Metadata field consists of field name, default value and other configurations  • Customised fields viewed on user interface for variable data input		
Scan Features	Scan Build Job Compression Quality / File Size Control Original Type (Photo and Text, Photo, Text, Map, Newspaper / Magazine) Auto Background and Shadow Suppression TWAIN Support, WIA 2.0 Support		

Scan to Email (Standard)			
Scan Features	<ul> <li>Email signatures (6 lines each of 128 character max), email message body (user configurable), email CentreWare IS confirmation sheet options</li> <li>Scan to Email S/MIME Encryption</li> <li>Email signing (requires Smart Card option)</li> <li>Auto send to self</li> </ul>		
Directory Access	Address list via LDAP (Windows Active Directory, Exchange, Notes, Domino) Downloaded address list (comma-separated file format)		
Scan to (Standard)			
Features	Scan to USB Scan to Network Folder (uses Unified Address Book entries)		
Network Scanning – Software Sol	utions		
Xerox® Scan to PC Desktop® Professional (Optional)	A desktop offering that provides advanced document imaging, archiving, editing and organisation tools:  • PaperPort Professional image viewing and file management software  - Complete PDF functionality  - Secure PDF workflow of all scanning applications  • OmniPage Pro Office (for desktop/client installation) – Professional OCR software for digital archiving and document conversion  • Image Retriever – provides fully automated retrieval of scanned images direct from a scan enabled Xerox® WorkCentre to individual desktops. Also includes email inbox polling capability		
Xerox® ConnectKey for DocuShare® (Optional)	Xerox® ConnectKey for DocuShare, a one-step scan-to-workflow solution, simplifies the process of incorporating hard copy content into enterprise document flows. Users can easily scan documents directly into a DocuShare collection or Windows folder via a multifunction printer.		
Xerox <sup>®</sup> ConnectKey <sup>®</sup> Apps (Found at the Xerox <sup>®</sup> App Gallery)	Increase user productivity by simplifying and shortening everyday tasks. Unlike traditional software, ConnectKey Apps do not require a dedicated server, PC or IT resource. Instead, simply download these lightweight, serverless ConnectKey Apps to the ConnectKey-enabled multifunction printer.		
Security			
Features	<ul> <li>Expanded Authentication</li> <li>Network authentication to access device and/or device services via- Kerberos (UNIX / Windows Server 2003 / Windows Server 2008), SMB (Windows Server 2003 / Windows Server 2008), NDS, LDAP authentication</li> <li>Local Authentication (internal database)</li> <li>Smart Card authentication -144k CAC / PIV Card Support (2048 bit certificate key) / .NET</li> <li>Secure Data</li> <li>Digitally signed PDF (when using Smart Card authentication)</li> <li>Encrypted Scan to Email</li> <li>Encrypted / Password Protected PDF (when using Email and Network Scan Templates only)</li> <li>Secure Print (up to 10 digit PIN or Network Authentication)</li> <li>Immediate Image Overwrite / Securely delete jobs using approved algorithms</li> <li>On Demand Image Overwrite (Scheduled, Manual), includes sanitation of unused area of disk</li> <li>FIPS 140-2 256 bit Hard Disk Encryption</li> <li>Expanded Authorisation</li> <li>SA access based on network credentials</li> <li>Authorisation per user per service</li> <li>User Permissions required to access Print and Print Features (e.g. colour access, or time restrictions) reflects in the print driver</li> <li>Secure Network Access</li> <li>IP Filter, IPsec, IPv6, TLS v1.0, v1.2, SNMPv3, HTTPS, 802.1X, Cisco® TrustSec Identity Services Engine integration, Device Security</li> <li>McAfee® Embedded Security, Port disablement including USB ports, Audit Log, Hide Print Job Names, McAfee Integrity Control (optional)</li> <li>Common Criteria Certification ISO 15408 (undergoing evaluation)</li> </ul>		
Xerox® PrintSafe Software	This authentication software integrates with trusted industry cards and readers and provides PIN access to nearly any printer in a customer's secured print environment. It works with both Xerox® devices and devices from other vendors. This software is open to work with a variety of industry standard secure readers and cards.		
Fax			
Walk-up Embedded Fax³, LAN Fax	, Internet Fax (includes LAN Fax (Fax forward to Email or SMB)), Network Server Fax Enablement		
Fax Speed	Up to 33.6 Kbps (analogue)		
Memory	Uses device memory		
Resolution	Up to 600 x 600 dpi (Super Fine) resolution Up to 200 x 200 dpi (Fine) resolution Up to 200 x 100 dpi (Standard) resolution		
Compression	MH, MR, MMR, JBIG		
Fax Features	Duplex Scanning Reports Auto Redial Auto Reduction Cover Page Delayed Send Fax Forward to Email Memory Receive Polling Secure Fax Speed Dials (up to 200 individual, 100 group)		

Device Management			
Management Support	SNMP Version 1. SNMP Version 2c and SNMP Version 3 trap over TCP/IP and IP		
тападетен эцрроп	MIB access (IETF-MIBII RFC 1213), Host Resources MIB RFC 2790, Printer MIB RFC 1759 v.2		
Xerox® CentreWare® Web	A Web-based server application for network administrators that permits Web browser-based device management from any workstation, whether running Windows, UNIX or any other operating system:  Works with any SNMP-managed printer from any manufacturer.  Provides help with device discovery and installation, health checks and troubleshooting, and device upgrades, as well as basic accounting and asset management.  Requires Windows 8, Vista, Server 2009, Server 2012 or Windows 7 and Internet Explorer 8.x and higher.  CentreWare Integration available for Tivoli® NetView®, Unicentre TNG®, Microsoft Management Console (MMC), HP® OpenView®		
Novell NDPS/NEPS	Server gateway application: centralised management tool.		
Xerox® Device Manager	Xerox® Device Manager collects and manages the data that drives fact-based decisions for your enterprise device management environment. It is a single tool to install print queues and configure, manage, monitor and report on both networked and locally connected devices – regardless of vendor – across your enterprise. Xerox® Device Manager provides:  • Device monitoring and troubleshooting  • Extensive reporting and discovery of new devices  • Usage collection, chargeback and billing capabilities		
Xerox® Device Types for SAP Environment	Xerox, together with SAP through our Gold-level membership in the SAP Printer Vendor Programme, provides seamless connectivity between SAP systems and your Xerox® printers and multifunction printers. And as an SAP customer you benefit from having SAP-certified Xerox® device types available right from SAP's online delivery model. SAP-certified device types for Xerox® printers and multifunction printers are available to download. www.office.xerox.com/software-solutions		
Xerox® Device Types for SAP R/3 Intelligent Barcode Utility (optional)	Provides built-in process intelligence that allows the printing of barcodes on any appropriately configured PostScript printer in specific versions of SAP environment and within Latin-1 (ISO8859-1) SAP system code pages only. Used in conjunction with Xerox® PostScript Device Types for SAP environment and Xerox® Font Centre Barcode Fonts. Information available at <a href="https://www.office.xerox.com/software-solutions">www.office.xerox.com/software-solutions</a>		
Xerox® Barcode Pro PS (optional)	Enables intelligent PostScript printing on Xerox® multifunction printers by storing Xerox® software, as well as, the barcode fonts on the printer hard disk. Enables the printing of barcodes from any application (SAP client or mainframe) that supports PostScript printing. Information available at www.office.xerox.com/software-solutions		
CentreWare Internet Services – Int	egrated Web Pages Provided by the Device		
Device Status	Web server embedded in Network Controller:  Tray status/contents Consumables status Alerts Remote Control Panel		
Job Submission	Print ready files: PS, PCL, TIFF, PDF, JPG, XPS, TXT, PRN Output feature selection (2-sided, output colour, collate, orientation, staple, hole punch, folding, output destination) Delivery options (Immediate, sample set, delay and secure, Save job or reprint)		
Device Administration	Allows simple, remote installation setting of configuration options and management of the device		
Browsers	Internet Explorer 7.x, 8.x, 9.x Safari 5.x Mozilla Firefox 4.x, 5.x, 6.x, 7.x, 8.x, 9.x, 10.x, 11.x Opera 11.x Chrome 12		
Support	Install print / scan drivers and online support available via web page		
Languages Supported	International English, International French, Italian, German, International Spanish, Dutch, Brazilian Portuguese, Swedish, Norwegian, Danish, Finnish, Russian, Simplified Chinese, Korean, Japanese, Arabic		
Remote Services			
Xerox® MeterAssistant®	Automates the process of collecting and submitting meter reads for tracking and billing of Xerox® device usage. Eliminates the need for time-consuming end-user involvement and ensures that meter reads are submitted to Xerox on time.		
Xerox® SuppliesAssistant®	Automatically orders supplies for Xerox® output devices based on actual usage, eliminating the need to manually manage supplies inventory.		
MaintenanceAssistant	Offers a fast (and free) way to resolve potential issues and receive assistance and automate the troubleshooting/repair process. Diagnostic data is sent to Xerox, allowing for problems to be solved faster with increased uptime.		
Accounting			
Xerox® Standard Accounting (Stand			
Tracking	Copy, Print, Fax, Scan and Email usage		
Accounting	Up to 2,497 User accounts (User ID) Up to 500 General accounts (Client) Up to 498 Group accounts (Department)		
Features	<ul> <li>Administrator can manage the feature via the Web User Interface or device control panel in tools</li> <li>Administrator has the ability to import or export user accounts, Group Accounts, General Accounts and User limits via an industry standard CSV file</li> </ul>		
Accounting Options – Network Acc	ounting (Allows central server to manage all accounting)		
	<ul> <li>Enhanced network accounting with up to the minute data on how the system is being used</li> <li>Comprehensive management and enterprise scale tracking and reporting of device usage of copy, print, scan and server fax</li> <li>Numerous solutions are available through Xerox Alliance Partners. For details visit www.xerox.com</li> <li>Security enhancements with the addition of HTTPS protocol support</li> <li>Device requests account authentication from third party server enabling larger databases of users and accounts</li> <li>Accept Authentication Login at control panel and pass to third party Networking Account</li> <li>Interface with third party accounting terminal for accounting user interface</li> </ul>		

What Comes in the Box			
	WorkCentre 6655i Colour Multifunction Printer  Starter Toner Cartridges – One of each (Cyan, Magenta, Yellow: 3,000 print capacity <sup>6</sup> ; Black: 6,000 print capacity <sup>6</sup> )  Quick Installation Guide, Product Information Guide, Driver CD, Documentation CD (User Manual, System Admin Guide)  Power Cable  Fax Cord		
Supplies and Accessories	Description	Quantity	Part Number
Supplies	Black Toner Cartridge	12,000 std. pages <sup>6</sup>	106R02755
	Cyan Toner Cartridge	7,500 std. pages <sup>6</sup>	106R02752
	Magenta Toner Cartridge	7,500 std. pages <sup>6</sup>	106R02753
	Yellow Toner Cartridge	7,500 std. pages <sup>6</sup>	106R02754
	Staple Cartridge	3,000 staples	108R00823
Routine Maintenance Items	Imaging Unit Kit	Up to 60,000 pages <sup>7</sup>	108R01121
	Waste Cartridge	Up to 30,000 pages <sup>7</sup>	108R01124
	Fuser Assembly (110V)	Up to 100,000 pages <sup>7</sup>	115R00088
	Fuser Assembly (220V)	Up to 100,000 pages <sup>7</sup>	115R00089
	Transfer Unit Kit	Up to 100,000 pages <sup>7</sup>	108R01122
Accessories	550-sheet Feeder (Adjustable up to A4 / legal)	-	097S04664
	Stand (Adds storage capacity for supplies, device stability, mobility and 13.1 in. of height)	-	497K14670
	Wireless Networking Adapter	-	497K11500
	McAfee Integrity Kit	-	320S00665
	Common Access Card Enablement Kit	-	498K17546

<sup>&</sup>lt;sup>1</sup> Maximum volume capacity expected in any one month. Not expected to be sustained on a regular basis.

Return spent imaging supplies through the Xerox Green World Alliance collection/reuse/recycling programme. For more information, visit <a href="https://www.xerox.com/about-xerox/recycling">www.xerox.com/about-xerox/recycling</a>.

Build and configure your own Xerox® WorkCentre 6655i Colour Multifunction Printer at www.buildyourownxerox.com/connectkey.

For more information, visit us at www.xerox.com/office



<sup>&</sup>lt;sup>2</sup> Expected regular monthly throughput.

<sup>&</sup>lt;sup>3</sup> Requires analog phone line.

<sup>4</sup> Power states defined per ENERGY STAR® Programme requirements for Imaging Equipment.

<sup>&</sup>lt;sup>5</sup> Paper capacities are based on 20 lb. / 75 gsm stock; capacities will vary with different weight stocks.

<sup>6</sup> Average standard pages. Declared Yield in accordance with ISO/IEC19798. Yield will vary based on image, area coverage and print mode.

<sup>7</sup> Approximate pages. Declared Yield based on letter-/A4-size 20 lb. (75 gsm) pages. Yield will vary based on media type, size, weight, orientation, and usage patterns.